

GLOBE RAM

DEMOLITION & CRUSHING EQUIPMENT

Compactor



THE CONQUEROR OF EVERY ROCK

| Compactor | | | | | | | | |
|--------------------------------|---------------|-------|---------------|-------|---------------|-------|---------------|-------|
| Specifications | RM 605 | | RM 610 | | RM 620 | | RM 635 | |
| Working weight (incl. Bracket) | 150 | kg | 410 | kg | 800 | kg | 1300 | kg |
| | 330 | lbs | 900 | lbs | 1760 | lbs | 2870 | lbs |
| Optimum oil flow | 65 | l/min | 70 | l/min | 115 | l/min | 190 | l/min |
| | 17 | gpm | 18 | gpm | 30 | gpm | 50 | gpm |
| Max. Operating pressure | 140 | bar | 140 | bar | 140 | bar | 140 | bar |
| | 2000 | psi | 2000 | psi | 2000 | psi | 2000 | psi |
| Compacting frequency | 2850 | 1/min | 2100 | 1/min | 1600 | 1/min | 2000 | 1/min |
| | 2850 | 1/min | 2100 | 1/min | 1600 | 1/min | 2000 | 1/min |
| Height (excl. bracket) | 460 | mm | 460 | mm | 575 | mm | 620 | mm |
| | 18 | in. | 18 | in. | 22,5 | in. | 24,5 | in. |
| Base plate width | 300 | mm | 585 | mm | 600 | mm | 890 | mm |
| | 12 | in. | 23 | in. | 23,5 | in. | 35 | in. |
| Base plate length | 735 | mm | 840 | mm | 1020 | mm | 1210 | mm |
| | 29 | in. | 33 | in. | 40 | in. | 47,5 | in. |
| Impulse force | 2215 | kg | 3445 | kg | 4835 | kg | 10765 | kg |
| | 4880 | lbs | 7590 | lbs | 10660 | lbs | 23730 | lbs |
| Advised carrier weight | 1 - 6 | t | 4 - 10 | t | 9 - 22 | t | 21 - 46 | t |
| | 1,1 - 6,6 | tons | 4,4 - 11 | tons | 10 - 24 | tons | 23 - 51 | tons |