

GLOB RAM

DEMOLITION & CRUSHING EQUIPMENT

Steel shear



THE CONQUEROR OF EVERY ROCK

www.globram.com

Steel shear - Hydraulic rotation



Specifications	RM 911R		RM 914R		RM 924R		RM 928R		RM 944R		RM 959R		RM 968R		RM 979R	
Working weight (incl. bracket)	950	kg	1820	kg	2800	kg	3710	kg	5570	kg	7070	kg	8300	kg	10400	kg
	2090	lbs	4010	lbs	6170	lbs	8180	lbs	12280	lbs	15590	lbs	18300	lbs	22930	lbs
Optimum oil flow / open-close	180	l/min	200	l/min	250	l/min	300	l/min	350	l/min	400	l/min	450	l/min	500	l/min
	48	gpm	53	gpm	66	gpm	79	gpm	92	gpm	106	gpm	119	gpm	132	gpm
Max. operating pressure / open-close	300	bar	350	bar	350	bar	350	bar	350	bar	350	bar	350	bar	400	bar
	4350	psi	5080	psi	5080	psi	5080	psi	5080	psi	5080	psi	5080	psi	5800	psi
Optimum oil flow / rotation	20	l/min	20	l/min	30	l/min	30	l/min	40	l/min	40	l/min	40	l/min	50	l/min
	5,3	gpm	5,3	gpm	7,9	gpm	7,9	gpm	11	gpm	11	gpm	11	gpm	13	gpm
Max. operating pressure / rotation	140	bar	140	bar	140	bar	140	bar	120	bar	120	bar	120	bar	150	bar
	2030	psi	2030	psi	2030	psi	2030	psi	1740	psi	1740	psi	1740	psi	2180	psi
Max. jaw opening	320	mm	500	mm	560	mm	660	mm	720	mm	770	mm	890	mm	980	mm
	12,6	in.	19,7	in.	22,0	in.	26,0	in.	28,3	in.	30,3	in.	35,0	in.	38,6	in.
Jaw Depth	395	mm	535	mm	585	mm	660	mm	810	mm	870	mm	960	mm	1060	mm
	15,6	in.	21,1	in.	23,0	in.	26,0	in.	31,9	in.	34,3	in.	37,8	in.	41,7	in.
Overall length (excl. bracket)	2030	mm	2510	mm	2850	mm	3180	mm	4000	mm	4250	mm	4600	mm	4800	mm
	79,9	in.	98,8	in.	112,2	in.	125,2	in.	157,5	in.	167,3	in.	181,1	in.	189,0	in.
Max. crushing force	261	t	405	t	646	t	787	t	901	t	1022	t	1246	t	1460	t
	288	tons	446	tons	712	tons	867	tons	993	tons	1126	tons	1373	tons	1609	tons
Advised carrier weight - stick mounted	9 - 14	t	18 - 25	t	28 - 39	t	38 - 48	t	49 - 65	t	66 - 84	t	75 - 95	t	96 - 115	t
	10 - 15	tons	20 - 28	tons	31 - 43	tons	42 - 53	tons	54 - 72	tons	73 - 93	tons	83 - 105	tons	106 - 127	tons
Advised carrier weight - boom mounted	7 - 10	t	11 - 16	t	18 - 23	t	24 - 30	t	30 - 39	t	40 - 52	t	47 - 60	t	60 - 83	t
	7,7 - 11	tons	12 - 18	tons	20 - 25	tons	26 - 33	tons	33 - 43	tons	44 - 57	tons	52 - 66	tons	66 - 91	tons